



**KODAK**

Universal Satin Poly Poster / 8 mil

## Excellent Color Saturation for Advertising Displays

KODAK Universal Satin Poly Poster is ideal for advertising and displays that require excellent saturation and durable color. The tear- and water-resistant polypropylene features a hybrid inkjet coating optimized for dye ink and thermal inkjet printers, but is also compatible with the latest pigmented inks.

### FEATURES:

- Flexible, durable, tear-resistant base film
- Available in glossy and satin surfaces for a variety of viewing conditions
- Optimized for dye ink and thermal inkjet printers (expect slower dry times with pigmented inks)

### APPLICATIONS:

- Durable indoor banners
- Indoor posters
- Point of purchase displays

US Size	Quantity	SKU
36"x100'	1 Roll	084-00208B
42"x100'	1 Roll	084-00209B
50"x100'	1 Roll	084-00210B
60"x100'	1 Roll	084-00211B



# KODAK

## Universal Satin Poly Poster / 8 mil

Properties	Specifications
<b>Material</b>	Polypropylene
<b>Gauge</b>	7.7 mil, 155g
<b>Whiteness</b>	>90
<b>Tear Strength</b>	NA
<b>Printer/Ink Compatibility</b>	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
<b>Software Setting</b>	The photo gloss paper setting in most RIPs is appropriate; however, we recommend a custom ICC. The coating is engineered for more than 300% ink coverage. A photo gloss, satin or semi-gloss setting is recommended as a starting point. However, a custom ICC profile is ideal for optimal results.
<b>Light Fastness</b>	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
<b>Optimal Service Environment</b>	59-86° F , 20-70% R.H.
<b>Finishing/Post Processing</b>	It is recommended that you protect the printed side by mounting under glass, laminating, clear coating, or using photographic sleeves. This will help ensure image durability and stability. Pressure sensitive laminates provide the best bond. Applying the laminate by hand is not recommended.
<b>Handling Recommendations</b>	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.
<b>Ideal Storage Conditions</b>	68° F (20° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
<b>Shelf Life</b>	1 year from the BMG ship date when stored in proper conditions.



AMS: 888-893-4668  
EMEA: +34 935 479 700  
APJ: +61 2 8038 5013

**KodakWFMedia.com**

The Kodak trademark, logo, and trade dress are used under license from Kodak.

© 2017, Brand Management Group

