

# JUST daylight 5000 proGraphic | 18 W

fluorescent lamp, 18 Watt, 590 mm, 5000 Kelvin

#### **Product benefits**

- corresponding to ISO 3664 (when used in appropriate fixtures)
- minimal deviation of colour coordinates
- Low metamerism index;
  quality class in accordance with CIE 51.2: BC or better
- Measurement reports accoarding to all requirements
- suitable for conventional and electronic starter device technology
- dimmable

### Fields of application

- Visual matching of coloured surfaces, prints hardcopy & softcopy proofs
- Quality inspection & assurance
- Graphical & print industry, photographers, advertising agencies

## Colormetric properties

Color rendering indices		
Ra	>93	
Metamerism indices		
Mi <sub>vis</sub>	<1	
$\mathrm{Mi}_{\mathrm{uv}}$	<1,5	
Photometric data		
CCT	5000	
Chromaticity Error	<0.005	
CIE 1964 10° average viewer		
х	0.3478	
у	0.3595	

#### Technical data

Electrical data	
Rated wattage	18 W
Energy efficiency class	В
Energy consumption	22 kWh/1000 h
Luminous efficacy	53 lm/Watt
Nominal luminous flux	990 lm
Light colour EN12464-1	Daylight 5000
Additional product details	
Bases	G13 (T8)
Mercury content	4 mg
Apprpriate disposal according to WEEE	Yes
Nominal lifespan	20.000 h
Operating life	2.500 h
Weights and measures	
Lamp diameter (d)	26 mm
Length with bases (excl. base pins) (I)	590 mm
Weight	70,0 g



