



# KODAK

Backlit Film, Glossy / 8 mil / Solvent

## Vibrant light box applications

### Vibrant color

Compatible with solvent, eco-solvent and UV-curable printers, KODAK Backlit Film, Glossy / 8 mil / Solvent is a gloss-coated polyester backlit film used to produce vibrant light box applications.

### Heavy and rigid for smooth production

The heavyweight front-print backlit film is a durable polyester with exceptional color saturation that dries quickly to ensure easy handling and finishing in production.

### Applications:

- Backlit airport signage
- Backlit mall and shopping center signage
- Non-backlit display applications

US Size	Euro Size	Quantity	SKU
36" x 100'	91,4 cm x 30,5 m	1 Roll	KBLGS36
50" x 100'	127 cm x 30,5 m	1 Roll	KBLGS50
60" x 100'	152,4 cm x 30,5 m	1 Roll	KBLGS60

Certified for  
HP Latex Inks



# KODAK

Backlit Film, Glossy / 8 mil / Solvent

Properties	Specifications
<b>Material</b>	Polyester film
<b>Gauge</b>	8 mil
<b>Base Weight</b>	280g
<b>Gloss Level</b>	>=35
<b>Whiteness</b>	>92 CEI
<b>Printer/Ink Compatibility</b>	Compatible with solvent and eco-solvent inks.
<b>Software Settings</b>	Please refer to <a href="http://KodakWFMedia.com">KodakWFMedia.com</a> for ICC profiles for some printers.
<b>Finishing/Post Processing</b>	It is always recommended that a protective laminate be applied after printing. Hand applying a laminate is not recommended. Pressure-sensitive can be used. Before applying the laminate, allow the image to dry for 24 hours.
<b>Optimal Service Environment</b>	72° F (21° C), 50% R.H. For end use: 0-300° F.
<b>Handling Recommendations</b>	It is suggested that you use the take-up reel with this product as the product could have a slight static charge that can cause the product to stick to the post heaters. It is also recommended that media clips are used to keep the media from bunching up if static is present. Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
<b>Ideal Storage Conditions</b>	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
<b>Shelf Life</b>	1 year from the BMG ship date when stored in proper conditions.



AMS: 888-893-4668  
EMEA: +34 935 479 700  
APJ: +61 2 8038 5013

**KodakWFMedia.com**

The Kodak trademark, logo, and trade dress are used under license from Kodak.

© 2018, Brand Management Group

