



KODAK

Premium Rapid-Dry White Film, Matte / 5 mil

Water-resistant, long lasting prints

Superior opacity

Ideal for applications that require opacity, KODAK Premium Rapid-Dry White Film, Matte / 5 mil is a water-resistant polyester with a bright-white printable surface that maximizes color fidelity and accuracy.

Smudge- and scratch- resistant

It's black backing makes it 100% opaque. Compatible with dye and pigmented inks, it won't smudge or show fingerprints, and is also scratch- and abrasion-resistant.

FEATURES:

- Back coating provides full opacity
- Water-resistant, bright-white surface
- Scratch-, smudge- and abrasion-resistant

APPLICATIONS:

- Banner stand graphics
- Trade show and retail displays
- Special event and traveling displays

US Size	Euro Size	Quantity	SKU
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPRDWF36
42" x 100'	106,7 cm x 30,5 m	1 Roll	KPRDWF42
50" x 100'	127 cm x 30,5 m	1 Roll	KPRDWF50



KODAK

Premium Rapid-Dry White Film, Matte / 5 mil

Properties	Specifications
Material	Matte PET Film
Gauge	5 mil, 170g
Base Weight	280g
Gloss Level	>=35
CIE Whiteness	90
Opacity	>100
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigmented inks.
Software Settings	The coating on this product is engineered for better than 300% ink coverage. A film setting in most RIPs is appropriate. However, we recommend a custom ICC profile for optimal results. Please refer to www.brandmanagementgroup.com for ICC profiles for some printers.
Light-fastness	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
Finishing/Post Processing	It is recommended that you protect the printed side by mounting under glass, laminating, clear coating, or using photographic sleeves. This will help ensure image durability and stability. Pressure sensitive laminates provide the best bond. Applying the laminate by hand is not recommended.
Optimal Service Environment	72° F (21° C), 50% R.H. For end use: 0-300° F.
Handling Recommendations	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.



AMS: 888-893-4668
EMEA: +34 935 479 700
APJ: +61 2 8038 5013

KodakWFMedia.com

The Kodak trademark, logo, and trade dress are used under license from Kodak.

© 2017, Brand Management Group

