

### **KODAK** Production Matte Paper / 170g

# Low Cost, High Impact Graphics

#### High-quality, low cost

KODAK Production Matte Paper / 170g provides users the ability to print highquality, low-cost photos on a smooth, bright white surface.

#### Saturated color

It provides high ink-load retention needed for saturated colors, quality images, and brilliant colors and can be thermally laminated, making it ideal for producing high-impact graphics.

#### **Retail applications**

t is often used by shops who want a lowcost way to produce high volumes of pointof-purchase displays, posters, or color accurate renderings.

#### FEATURES:

- Compatible with dye and pigmented ink
- Versatile, covering the application spectrum
- Thermal laminate compatible

#### **APPLICATIONS:**

- Architectural renderings and presentation graphics
- High-volume point-of-purchase
- High-volume posters

US Size	Euro Size	Quantity	SKU
24" x 100'	61,0 cm x 30,5 m	1 Roll	KPMP24
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPMP36
42" x 100'	106,7 cm x 30,5 m	1 Roll	KPMP42
50" x 100'	111,8 cm x 30, 5 m	1 Roll	KPMP50
60" x 100'	152,4 cm x 30,5 m	1 Roll	KPMP60



### **KODAK** Production Matte Paper / 170g

Properties	Specifications	
Material	Matte photo paper	
Gauge	7 mil, 170g	
CIE Whiteness	150	
Opacity	>63	
Printer/Ink Compatability	Dye/Pigment	
Software Setting	The bond or uncoated paper setting in most RIPs is a recommended starting point. However, a custom IC profile is ideal for optimal results.	
Light Fastness	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resis- tant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.	
Finishing/Post Processing	It is recommended that you protect the printed side by mounting under glass, laminating, clear coating, or using photographic sleeves. This will help ensure image durability and stability. Pressure sensitive laminates provide the best bond. Applying the laminate by hand is not recommended.	
Handling Recommendations	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.	
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging	
Shelf Life	1 year from the BMG ship date when stored in proper conditions.	

## **BRAND**management**GROUP**

AMS:888-893-4668EMEA:+34 935 479 700APJ:+61 2 8038 5013

#### KodakWFMedia.com

The Kodak trademark, logo, and trade dress are used under license from Kodak.

© 2017, Brand Management Group

