# **PRODUCT DATA SHEET**

Rev 3 - Updated 5/19



# MAGIC SLEEK 6.5 mil prepasted wallcovering (*luster*)

## PRINTER COMPATIBILITY



#### **DESCRIPTION**

Magic SLEEK is a 6.5 mil high performance prepasted wallcovering reinforced with polymer for strength and durability. SLEEK has a bright white, ultra-smooth, matte printable surface allowing for pristine imaging. SLEEK is a fiber-based, 10% PCW substrate, making it a perfect alternative to vinyl. SLEEK is ideal for murals, wallcoverings, POP displays and decals.

## PHYSICAL CHARACTERISTICS

Thickness 6.5 mil
Basis Weight 165 g/m²
Opacity 96%
Gloss (60 4.5
Whiteness 80
Brightness 86

Fire Rating ASTM E84 Class A

\*All values are targets

# **FEATURES AND BENEFITS**

- Prepasted wallpaper
- Exclusive Magic® coating
- PVC free
- Washable/scrubbable surface
- ASTM-E84 (smoke generation and flame spread)
- Durable finish
- Excellent print performance
- Excellent ink adhesion
- Excellent black density and color pop
- Easy to install
- Tear resistant
- Water resistant
- Scratch resistant
- Fade resistant
- 10% post consumer waste

#### **COMMON APPLICATIONS**

- Wallcovering
- Wall murals
- Wall décor
- Maps
- Décor art reproductions

#### **PROCESSING TIPS**

- Preferred side out

# **FINISHING & PRINTING**

- Set printer for highest print quality
- Liquid laminates are recommended for wallcovering
- Visit www.magicinkjet.com
- Media profiles
- "Tips & Tricks" Wallcovering Installation

#### SHELF LIFE

2 years from ship date

#### **STORAGE CONDITIONS**

Temperature 50-85° F (10-30° C)

Relative Humidity 30-65%

#### **OPTIMAL PRINTING ENVIRONMENT**

Temperature 50-85° F (10-30° C)

Relative Humidity 30-65%

121 Kelsey Lane | Suite G | Tampa, Florida 33619 800-854-2341 | customerservice@dietzgen.com www.magicinkjet.com | my.dietzgen.com © Dietzgen Corporation

