

Pole Banner Select is a double-sided, durable, blockout banner material designed for indoor or outdoor applications. The material offers a matte finish and is ideal for application where complete opacity is required. Pole Banner Select is compatible with solvent, eco-solvent and UV ink. Available in widths from 38” - 196”.

### Material Details

| CHARACTERISTICS           | TEST METHOD                  | METRIC            | ENGLISH                |
|---------------------------|------------------------------|-------------------|------------------------|
| Total Weight              | DIN53352 BS3424<br>Method 5A | 610 gsm           | 18 oz./yd <sup>2</sup> |
| Denier                    |                              | 840 x 840 D       |                        |
| Base Fabric               |                              | Polyester         |                        |
| Thickness                 | DIN EN ISO 2286-3            | 0.46 mm           |                        |
| Tensile Strength          | DIN53352 BS 3424             | 1350 x 1200 N/5cm | 154.17 x 137.04 lbs/in |
| Tear Strength (warp/weft) | DIN53356 BS3424              | 245 x 185 N       | 55 185x 41.59 lbs      |
| Adhesion                  | DIN53357 BS3425              | 60 N/5CM          | 6.85 lbs/in            |
| Temperature Resistance    | DIN53357 BS3425<br>Method 10 | - 20 – 70 °C      |                        |

### Applications

|              | Back-lit | Banner | Billboard | Block-out | Building Wrap | Display Systems | Truckside |
|--------------|----------|--------|-----------|-----------|---------------|-----------------|-----------|
| Applications |          | ■      | ■         | ■         |               | ■               | ■         |

### Ink Printability

| Solvent | Eco Solvent | UV | Latex | Screen Printing | Dye Transfer | Dye Direct |
|---------|-------------|----|-------|-----------------|--------------|------------|
| ■       | ■           | ■  |       |                 |              |            |

### Available Sizes

| Metric (m)                  | English (inches)       |
|-----------------------------|------------------------|
| 0.965, 1.37,<br>1.60, 3.20, | 38”, 54”,<br>63”, 126” |

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. A weight variance of +1/-2 is acceptable. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)