



Product Specification
Commercial technical data sheet

Article Reference:	2218	
Article Name:	Half Panama	
Composition:	100% Cotton	
Loomstate Weight:	230 gsm	(+/- 5%)
Width:	60"	(+/- 3%)
Piece Lengths:	50mts (54.5 yards) as standard (No Joins)	
Finish:	Optic	Uncoated / Coated
Printing Ink Types:	Pigment*	

PREMEX SOLUTIONS NORTH AMERICA
771 Shallowford Road, Suite 102
Kennesaw, Georgia 30144
678-342-6172
info@premexsolutions.com

PREMEX SOLUTIONS UK & EUROPE
Green Lane, Green Lane Industrial Estate
Stockport, Cheshire, SK4 2JR
+44 (161) 429 5770 tel
+44 (161) 429 5775 fax
enquires@premexsolutions.com

**This is intended as a guide only. Other ink type preps are available on request.*

Upholstery - Martindale Abrasion (12 kPa Load)		RH 65% +/-4% / Temp 20°C +/-2°C			
Sample	Results				Minimum Requirements
	Change in Shade @ 3,000 Revs = Grade 3-4				A - 35,000 REVS B - 12,000 - 30,000 REVS C - 4,000 - 10,000 REVS
Fabric Type FLAT WOVEN	HEAD 3 NO FABRIC BREAKDOWN @ 21,000 REVS FABRIC BREAKDOWN @ 23,000 REVS HEAD 4 NO FABRIC BREAKDOWN @ 26,000 REVS FABRIC BREAKDOWN @ 28,000 REVS HEAD 2 NO FABRIC BREAKDOWN @ 30,000 REVS FABRIC BREAKDOWN @ 32,000 REVS				
Overall Result	21,000 REVS				
Overall Performance Level	B				
BS 2543: 2004 Classification (Minimum levels for customer reference)					
	LD	GD	HD	GC	SC
Flat Woven	B - 15,000	B - 20,000	B - 25,000	B - 30,000	A - 40,000
Figured Weaves	B - 12,000	B - 15,000	B - 20,000	B - 30,000	A - 40,000
Woven/Flocked/Non-Woven Pile Fabrics	C - 15,000	C - 20,000	B - 25,000	B - 25,000	B - 30,000
Knitted	B - 15,000	B - 20,000	B - 25,000	B - 25,000	B - 30,000