




HP Clear Film



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Give your ideas a photo-realistic finish

Deliver high-quality, durable prints

Keep your projects on track and demonstrate the quality and professionalism of your work with this optically clear film. Produce multiple overlays and transparent images with excellent line quality and consistent, vivid color.

Accomplish more with consistent results every time

Look to this professional-quality film to present your professional best. Produce sharp line quality and consistent, vivid color with a film designed to provide excellent bleed control and strong ink adhesion to prevent ink transfer between overlays.

Keep a brisk pace from one project to the next

Meet your project deadlines. Compatible with a wide range of HP DesignJet printers using both Original HP pigment- and dye-based, this optically clear film provides high-quality, consistent image quality print to print and roll to roll.

Target customers	Applications	Benefits
Architects	Trade show and event displays	Sharp line quality; consistent, vivid color
Engineers	POP and retail displays	Excellent bleed control for sharp images
Geographic Information Systems (GIS) professionals	Geographic Information Systems (GIS)	Strong ink adhesion prevents ink transfer between layers
	Architecture (AEC) and engineering (MCAD)	Compatible with both Original HP pigment- and dye-based inks

Technical specifications



HP Clear Film

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

Ink compatibility	Original HP pigment- and dye-based inks for HP DesignJet printers			
Weight	156 g/m ² per ISO 536 Test Method			
Thickness	119 microns/4.7 mil per ISO 534 Test Method			
Opacity	8% per TAPPI T-425 Test Method			
Brightness	>95 per TAPPI T-452 Test Method			
Whiteness	130 per CIE Ganz 82 Test Method			
Finish	Matte			
Operating temperature	15 to 35° C / 59 to 95° F			
Operating humidity	20 to 70% RH			
Dry time	Less than 9 minutes (at 23° C, 50% RH)			
Shelf life	2 years, unopened in original packaging			
Storage temperature	5 to 40° C / 41 to 104° F			
Storage humidity	10 to 80% RH			
Country of origin	Product of Germany			
Ordering information	Product numbers	Roll sizes	UPC Codes	Region
	C3876A ¹	610 mm x 22,9 m (24 in x 75 ft)	848412012736	Worldwide
	C3875A ¹	914 mm x 22,9 m (36 in x 75 ft)	848412012743	Worldwide
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see HPLFMedia.com/MediaWarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .			

¹ Requires 2-inch spindle for compatibility with the HP Latex 260, HP DesignJet L25500 and L26500 Printer series.

For detailed information on the HP large format printing materials portfolio and to order, see HPLFMedia.com

