# HP Coated Paper





## The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



## **Create presentation-quality images**

#### Accomplish more with consistent results

From line drawings to illustrations and light ink-density graphics, see high-quality, consistent image quality print to print and roll to roll.

#### Improve your response time

Handle prints with confidence right off the printer. An enhanced coating provides ink abrasion resistance to help you deliver on quick turnaround times.

#### Do more, with the environment in mind

Gain versatility with this premium bright white paper. From working comps and design proofs to fine line drawings and illustrations, meet the project needs and the environmental objectives of your company and clients with this recyclable  $^1$ ,FSC $^9$ -certified paper.

Target customers	Applications	ers and presentations Crisp text and graphics, consistent high-quality results		
Architects	Posters and presentations			
Engineers	POP and retail displays			
Geographic Information Systems (GIS) professionals	Geographic Information Systems (GIS)	Compatible with both Original HP pigment- and dye-based inks		
Graphic designers	Architecture (AEC) Engineering (MCAD)	Recyclable through commonly available programs <sup>1</sup>		
Print service providers		FSC®-certified paper2		

### **Technical specifications**



#### **HP Coated Paper**

For the latest ICC profiles/paper presets, please visit HPL FMedia.com/paperpresets.

	Original HP pigment- and dye-based inks for HP DesignJet printers					
Weight	90 g/m² per ISO 536 Test Method, (24 lbs)					
Thickness	114 microns/4.5 mil per ISO 534 Test Method					
Opacity	93% per TAPPI T-425 Test Method					
Brightness	89 per TAPPI T-452 Test Method					
Whiteness	145 per CIE Whiteness ISO 11475 D65/10° Outdoor Daylight Test Method					
Finish	Matte					
Operating temperature	15 to 35° C / 59 to 95° F					
Operating humidity	20 to 80% RH					
Dry time	Immediate (at 23° C, 50% RH)					
Lamination	Yes, with commercially available thermal and pressure-sensitive laminate films					
Shelf life	2 years, unopened in original packaging					
Storage temperature	0 to 40° C / 32 to 104° F					
Storage humidity	5 to 95% RH					
Environmental	Recyclable through commonly available recycling programs' and FSC®-certified paper.2					
Country of origin	Product of Germany UPC Codes Region					
Ordering information	Product numbers	Roll sizes				
	C6019B <sup>3</sup>	610 mm x 45,7 m (24 in x 150 ft)	848412012750	Worldwide		
	C6020B <sup>3</sup>	914 mm x 45,7 m (36 in x 150 ft)	848412012774	Worldwide		
	C6567B3	1067 mm x 45,7 m (42 in x 150 ft)	848412012798	Worldwide		
	C6568B3	1372 mm x 45,7 m (54 in x 150 ft)	848412012804	Worldwide		
	C6980A3	914 mm x 91,4 m (36 in x 300 ft)	848412012781	Worldwide		
	Q1443A	(A2) 420 mm x 45.7 m	848412014143	Japan		
		. ,	848412014150	Europe, Singapore		
	Q1442A	(A1) 594 mm x 45,7 m				


<sup>&</sup>lt;sup>1</sup> Can be recycled through commonly available recycling programs.

<sup>&</sup>lt;sup>3</sup> Requires 2-inch spindle for compatibility with the HP DesignJet L25500 and L26500 Printer series.





 $For detailed information on the HP large format print media portfolio and to order, visit \\ \frac{\text{HPLFMedia.com}}{\text{com}}$ 





<sup>&</sup>lt;sup>2</sup> HP has a policy for offering Forest Stewardship Council\* (FSC\*)-certified papers that are sourced from FSC\*-certified forests and other controlled sources. BMG trademark license code FSC\*-C115319, see fsc.org. HP trademark license code FSC\*-C017543, see fsc.org. Not all FSC\*-certified products are available in all regions. For information about HP large format printing materials, please visit HPLFMedia.com.