



KODAK PROFESSIONAL

Inkjet Artist Matte Canvas

High-quality canvas, fine-art results

Water-resistant matte finish

KODAK PROFESSIONAL Inkjet Artist Matte Canvas is a medium textured, 2-over-1 weave, poly/cotton blend canvas that features a water-resistant matte finish.

The latest printer and ink technology

This high-quality canvas is perfect for fine art and photographic reproductions utilizing the latest dye and pigmented inks.

APPLICATIONS:

- Gallery wraps
- Mounted canvas prints
- Fine art reproduction

FEATURES:

- Poly/cotton blend canvas
- Medium textured, 2-over-1 weave
- Compatible with dye and pigment inks

| US Size | Euro Size | Quantity | SKU |
|-----------|--------------------|----------|-----------|
| 17" x 40' | 43,2 cm x 12,19 m | 1 Roll | KPROTMC17 |
| 24" x 40' | 61,0 cm x 12,19 m | 1 Roll | KPROTMC24 |
| 36" x 40' | 91,4 cm x 12,19 m | 1 Roll | KPROTMC36 |
| 44" x 40' | 111,8 cm x 12,19 m | 1 Roll | KPROTMC44 |
| 60" x 40' | 154,2 cm x 12,19 m | 1 Roll | KPROTMC60 |



KODAK PROFESSIONAL

Inkjet Artist Matte Canvas

| Properties | Specifications |
|------------------------------------|--|
| Material | 65% polyester, 35% cotton base |
| Fabric Weave | 2 x 1 weave |
| Gauge | 18 mil |
| Base Weight | 410g |
| Whiteness | >100 CEI |
| Printer/Ink Compatibility | Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks. |
| Software Setting | The coating is engineered for more than 300% ink coverage. A Heavy Weight Coated or Enhanced Matte setting is recommended as a starting point. However, a custom ICC profile is ideal for optimal results. |
| Light Fastness | Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer. |
| Optimal Service Environment | 66-77° F , 20-60% R.H. |
| Finishing/Post Processing | No post processing or finishing is required, though a clear fixative may be applied to enhance certain areas of the print. |
| Handling Recommendations | Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out. |
| Ideal Storage Conditions | 70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging |
| Shelf Life | 1 year from the BMG ship date when stored in proper conditions. |



AMS: 888-893-4668

EMEA: +34 935 479 700

APJ: +61 2 8038 5013

KODAKWFMedia.com

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2023, Brand Management Group

