



KODAK Production Matte Paper, 170gsm

Low Cost, High Impact Graphics

High-quality, low cost

KODAK Production Matte Paper, 170gsm provides users the ability to print high-quality, low-cost photos on a smooth, bright white surface.

Saturated color

It provides high ink-load retention needed for saturated colors, quality images, and brilliant colors and can be thermally laminated, making it ideal for producing high-impact graphics.

Retail applications

KODAK Production Matte Paper, 170gsm is often used by shops who want a low-cost way to produce high volumes of point-of-purchase displays, posters, or color accurate renderings.

FSC®-certified

Meet environmental objectives with this FSC®-certified paper

FEATURES:

- Compatible with dye and pigmented ink
- Versatile, covering the application spectrum
- Thermal laminate compatible
- FSC®-certified paper

APPLICATIONS:

- Architectural renderings and presentation graphics
- High-volume point-of-purchase
- High-volume posters

US Size	Euro Size	Quantity	SKU
24" x 100'	61,0 cm x 30,5 m	1 Roll	KPMP24
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPMP36
42" x 100'	106,7 cm x 30,5 m	1 Roll	KPMP42
60" x 100'	152,4 cm x 30,5 m	1 Roll	KPMP60



KODAK Production

Matte Paper, 170gsm

Properties	Specifications
Material	Matte photo paper
Gauge	7 mil, 170g
CIE Whiteness	150
Environmental	FSC®-certified paper
Opacity	>63
Printer/Ink Compatability	Dye/Pigment
Software Setting	The bond or uncoated paper setting in most RIPs is a recommended starting point. However, a custom ICC profile is ideal for optimal results.
Light Fastness	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
Finishing/Post Processing	It is recommended that you protect the printed side by mounting under glass, laminating, clear coating, or using photographic sleeves. This will help ensure image durability and stability. Pressure sensitive laminates provide the best bond. Applying the laminate by hand is not recommended.
Handling Recommendations	Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging
Shelf Life	1 year from the BMG ship date when stored in proper conditions.



The mark of responsible forestry



AMS: 888-893-4668
EMEA: +34 935 479 700
APJ: +61 2 8038 5013

KODAKWFMedia.com

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2023, Brand Management Group

