



KODAK PROFESSIONAL
Inkjet Gloss Photo Paper, 255g

Next-generation paper for accurate color reproduction

The latest printer and ink technology

KODAK PROFESSIONAL Inkjet Gloss Photo Paper, 255 gsm has been updated to take advantage of the wider color gamut and improved ink technology of the latest generation of wide format inkjet printers from Canon, Epson and HP.

Accurate reproduction

This next-generation paper has a larger color gamut and higher Dmax to ensure that color captured in-camera reproduces more accurately, while producing deeper, richer black, an expanded dynamic range and additional detail in shadow areas.

FSC®-certified

Meet environmental objectives with this FSC®-certified paper.

APPLICATIONS:

- Wedding, portrait, landscape and exhibition photography
- High-end retail and display graphics
- Corporate and home décor

FEATURES:

- Expanded color gamut and higher Dmax
- Designed to take advantage of the latest printer and ink technology
- Engineered to lay flat with little to no curl
- FSC®-certified paper

US Size	Euro Size	Quantity	SKU
8.5" x 11"	21,59 cm x 27,94 cm	50 Sheets	KPRO8511G
*(A4) 8.3" x 11.7"	20,08 cm x 29,72 cm	50 Sheets	KPROA4G
*(A3+) 13" x 19"	33,02 cm x 48,26 cm	20 Sheets	KPROA3+G
17" x 100'	43,2 cm x 30,5 m	1 Roll	KPRO17G
24" x 100'	61,0 cm x 30,5 m	1 Roll	KPRO24G
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPRO36G
44" x 100'	111,8 cm x 30,5 m	1 Roll	KPRO44G
60" x 100'	152,4 cm x 30,5 m	1 Roll	KPRO60G

*Available in EMEA only



KODAK PROFESSIONAL

Inkjet Gloss Photo Paper, 255g

Properties	Specifications
Material	Resin-coated photo base
Gauge	10 mil / 255g
Gloss Level	>/=25
Opacity	>90%
Whiteness	>134
Environmental	FSC®-certified paper
Printer/Ink Compatibility	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
Software Setting	The photo gloss paper setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to KodakWFMedia.com for ICC profiles for some printers.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Hand applying laminate is not recommended. Pressure-sensitive or thermal laminates can be used. Before applying the laminate, allow the image to dry for 24 hours.
Optimal Service Environment	72° F (21° C), 50% R.H For end use: 0-300° F
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.



The mark of
responsible forestry



AMS: 888-893-4668

EMEA: +34 935 479 700

APJ: +61 2 8038 5013

KODAKWFMedia.com

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2023, Brand Management Group

