



KODAK

Gloss Backlit Film

Vibrant light box applications

Vibrant color

Compatible with solvent, eco-solvent, UV-curable and Latex 300 and 500 series printers, KODAK Gloss Backlit Film is a gloss-coated polyester backlit film used to produce vibrant light box applications.

Heavy and rigid for smooth production

The heavyweight front-print backlit film is a durable polyester with exceptional color saturation that dries quickly to ensure easy handling and finishing in production.

Applications:

- Backlit airport signage
- Backlit mall and shopping center signage
- Non-backlit display applications

US Size	Euro Size	Quantity	SKU
36" x 100'	91,4 cm x 30,5 m	1 Roll	KBLGS36
50" x 100'	127 cm x 30,5 m	1 Roll	KBLGS50
60" x 100'	152,4 cm x 30,5 m	1 Roll	KBLGS60

Certified for
HP Latex Inks

To download media presets and check compatibility with your HP Latex Printer, please visit the HP media locator website at hp.com/go/mediasolutionslocator



KODAK

Gloss Backlit Film

Properties	Specifications
Material	Polyester film
Gauge	8 mil
Base Weight	280g
Gloss Level	>=35
Whiteness	>92 CEI
Printer/Ink Compatibility	Compatible with solvent, eco-solvent and latex inks.
Software Settings	Please refer to KodakWFMedia.com for ICC profiles for some printers.
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Hand applying a laminate is not recommended. Pressure-sensitive can be used. Before applying the laminate, allow the image to dry for 24 hours.
Optimal Service Environment	72° F (21° C), 50% R.H. For end use: 0-300° F.
Handling Recommendations	It is suggested that you use the take-up reel with this product as the product could have a slight static charge that can cause the product to stick to the post heaters. It is also recommended that media clips are used to keep the media from bunching up if static is present. Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.

BMG BRANDmanagementGROUP

AMS: 888-893-4668

EMEA: +34 935 479 700

APJ: +61 2 8038 5013

KODAKWFMedia.com

The KODAK trademark, logo, and trade dress are used under license from KODAK.

© 2023, Brand Management Group

