Mid States Graphics

Window Perf ES 80/20

6 mil. Perforated pressure sensitive window film designed for short to mid-term applications. This product offers 20% open area.

Features and Benefits:

- Universal printability: UV-Curable, Solvent, Silk-Screen, & Latex inks
- ASTM E84 certified
- Easily removable up to 1 year under normal conditions (6 months no residue)
- Micro-perforation for superior image and view-through quality
- Polymeric vinyl features great dimensional stability
- Semi-permanent, clear adhesive is easy to remove

Part Number	Size	Core	Weight
ES-WP54100	54”x100’	3”	38 lbs.
ES-WP5425	54”x25’	3”	10 lbs.
ES-WP2710	27”x10’ Test Roll	3”	2 lbs.

Physical Properties:

Parameter	Value
Material	Perforated Polymeric Vinyl
Thickness	6 mil (145 microns)
Liner	Universal Paper Liner
Open Area	20% for maximum contrast and printing results
Adhesive	Removable acrylic based clear adhesive

Typical Characteristics:

Parameter	Value
Min. Application Temp	+50° F up to +90° F (+10° C up to +32° C)
Service Range Temp	0° F up to 140° F (-17° C up to 50° C)
Durability	1 year normal conditions. Clean removal within 6 months.
Adhesion may increase over time. Not to be applied on: fresh paint or ink, polycarbonate, certain PVC. For critical substrates, please test prior to use.	
Flammability	M1, B1, and ASTM E84 certified
Application	Avoid contact with solvent or ammonia based cleaners. Clean window with soap and water. Rinse and dry glass after cleaning. ALWAYS clean and dry surface before application.

Applications:

- ✓ Building Wraps
- ✓ Shop Windows

Compatibility: * Eco Sol * Solvent * UV * Latex

The above information is based on research believed to be reliable but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purchases.

Mid States Graphics, LTD
1700 Drake Ct
Hanover Park, IL 60133
T: 630-837-8571
Sales@myproofline.com
www.midstatesgraphicsltd.com