

Roland DGA GuardLam™ Embossed Floor Overlamine Film: ESM-GLEF**Product Overview**

Roland DGA GuardLam Embossed Floor Overlamine Film is UL-410 certified for floor applications. However, this 6-mil embossed, calendered film can be used for so many other applications requiring a textured finish, like counter mats, window graphics and wall graphics.

Specifications

Film Caliper: 6 mil
Finish: Matte, Embossed
Basis Weight: 0.44 msi
Adhesive: Acrylic
Liner: Clear Film

Liner Caliper: 2 mil
Core Diameter: 3"
Outdoor Durability: 6 months
Shelf Life: 1 year
Available Size: 20", 30", and 54" x 150'

Applications

Floor Graphics
Counters, Worktops and Décor
In-Store Graphics

Displays
Window Graphics
Indoor/Outdoor Signage

Part Number

ESM-GLEF-150-20
ESM-GLEF-150-30
ESM-GLEF-150-54

Storage Conditions

ESM-GLEF Roland DGA GuardLam Overlamine Film should be handled with care to prevent surface contamination that may affect the printable surface of the product. This material should be processed and stored in an environment of 65° - 85° F (18° - 29° C) and 30 - 50% relative humidity (non-condensing) that is clean and relatively dust-free. We recommend storing this product in its original packaging in a cool, dry area until ready for use. If storage conditions are outside the recommended operating ranges, allow the material to acclimate to the production environment for at least 24 to 48 hours before use.

Roland Certified Media Guarantee

This product is sold for the usage of the applications stated in this document. The product is free of defects when applied to printed calendered media. It is not compatible with cast vinyl.