

## Direct Transfer System Film Specifications

### Product Overview

Our premium Direct Transfer System film is for Direct to Film (DTF) applications. This is a dimensionally stable film that does not warp under heat. This anti-static film also provides clean transfers. Use this for your various DTF applications. It is compatible with our VersaSTUDIO BN-20D printers.

### Specifications

Face: 2.95 mil +/- 0.2 mils

Finish: Matte

Shelf Life: 1 Year unopened/ 6 months opened

Ink Compatibility: S-PG

Roll Size: 20" x 164'

Core: 3" core

### Applications

Apparel and accessories

Caps/Hats

Tote bags/bags

Fabric décor

### Part Number

S-F164 (20" x 164')

### Storage Conditions

Our Direct Transfer System Film should be handled with care to prevent surface contamination that may affect the printable surface of the product. It should be processed and stored in an environment of 65° - 85° F (18° - 29° C) and 30 - 50% relative humidity (non-condensing) that is clean and relatively dust-free. It is recommended to store this product in its original packaging in a cool dry area until ready for use. If storage conditions are outside the recommended operating ranges, allow the material to acclimate to the production environment for at least 24 to 48 hours before use.

### Roland Certified Media Guarantee

This product is sold for the usage of the applications stated in this document. The product is free of defects, and produces vibrant, printed graphics when used with Roland's S-PG inks and S-POWDER.

Imagine.