

# BUILT FOR PROFESSIONALS BY PROFESSIONALS



MADE  
IN JAPAN

## 24" XPD-924D DTF PRINTER



OEKO  
TEX®



**XPJ-1682D**

The STS Inks XPD-924D 24-inch DTF Printer boasts staggered dual AccuFine HD printheads for enhanced productivity, delivering high-quality transfers with smooth gradations and fine lines. As the fastest dual-head printer on the market, it maintains true quality and consistency in every print. Our new XPD-924 features a built-in white ink circulation system that operates continuously, ensuring a seamless flow of ink.

This advanced feature reduces the likelihood and the need for maintenance, resulting in increased uptime and greater profitability for our customers!

The XPD-924D is packed with standard features such as:

- Dropmaster 2 (Automatic Bi-Directional alignments),
- Feed Master (Automatic Feed Roller Adjustment),
- i-screen Print Effects- Multiple Waveforms that Mitigate Banding.
- Media Tracker (Roll Remainder Tracking)
- White Ink Circulation
- Auto Cleaning and Maintenance

The XPD-924D includes Digital Factory RIP 11 Software, bundled with the printer for the ultimate balance of speed and quality. Pre-installed high quality color profiles at various resolutions to match our ink and film make this printer instantly ready for production.




STS INKS® 8300 CONGRESS AVE. BOCA RATON, FL 33487  
TEL: 561-999-8818 | MAIL: SALES@STSINKS.COM  
WWW.STSINKS.COM

**STS**®  
DIRECT TO FILM

# XPD-924D

Powered by STS Inks®



COTTON AND  
POLYESTER



DENIM



FLEECE



NYLON

## FEATURES

- High-precision Heavyduty Aluminum Rail System for High Quality and Stable Printing.
- Ease-of-use Side Mounted LAN and Power Plugs and LED Operation Panel.
- New AccuFine HD Printheads Provide Faster Speeds with Exceptional Quality.
- Built-in Sensors for Operator-Driven Automatic Bi-directional and Page feed Alignments.
- Improved front Dryer system for 20% Faster Ink Dry Times.
- Updated Media Angles and Media Feeding Mechanism to Allow for Easy Loading and Page Feed for DTF Film.
- Internal LED lighting for Unobstructed Print Viewing and Maintenance Access.
- Includes the Mutoh Status Monitor (MSM) Companion Software for Convenience and Efficiency: Records Print History, Job Cost Analysis, Remote Access.
- Complete turnkey solutions that produce exceptional transfers that are super soft and colorful with excellent elasticity, and washability which creates the industry's finest hand feel transfers.

## SPECIFICATIONS

Printing method	Drop-on-demand Micro Piezo Inkjet Technology	Interface	Gigabit-Ethernet (1000BASE-T )	
Print head height	Four-level adjustment: 1.5mm, 2.0mm, 2.5mm, 4.0mm	Power Requirements	AC 100-220V ± 10%, 50/60Hz ± 1Hz	
Print head	2 (staggered)	Printing Environment	Temperature: 68-77°F / 20-26° C Humidity: 40-55%	
Max print resolution	1200x1200 dpi (1200/900/600/300 dpi print modes)	Power Consumption	Main: Operation status 700W or less Standby: 30W or less	
Media width	600 cm 25"	Dimensions (WxDxH)	Printer including stand: 70.68"x35.23"x56.48" cover closed	
Media capacity	ø 5.9" dia / 2" & 3" cores / Roll media 66lbs or less	Weight	Body: 310lb   Stand: 70.54lb / Body: 140kg  Stand: 32kg	
Max media thickness	Low 1 0.3mm, Low2 0.8mm, Mid. 1.3mm, High 2.8mm	INK	Type	DTF
Max printable width	24.5 in		Ink Set	4 color (CMYK)   White
Max print speed	17 sqm/hr - 183 sqf/hr		Volume	500ml Direct to Film Ink Cartridge XPD
RIP software	CADlink™ Digital Factory 11		No. of slots	6