

TexPrint DTxP TexPrint DTR heavy

DESKTOP DYE-SUBLIMATION PAPER

The world's number one selling desktop dye-sublimation paper, TexPrint®DTR and TexPrint®DTXP deliver excellent dimensional stability while absorbing the heaviest ink loads. Our desktop sheets dry quickly, eliminate offsetting, and produce the most vibrant color transfers. TexPrint®DT sheets provide consistent, high-quality printing every time!





FEATURES AND BENEFITS

Broadest selection of sheet sizes and desktop rolls

Get exactly the right size, put-up and pack needed for your production environment.

Lightweight

Paper coating designed to work with all Epson printers.

Heavyweight

Coating designed to work with Ricoh, Virtuoso and Epson printers.

Waste reduction

Available in individually boxed or bulk packaging. Volume users can save time and labor by ordering bulk packaging.

Quick-Dry coating

DT eliminates smudges and handling issues and dries quickly.

Recyclable

100% recvclable ingredients.

Works on hard and soft applications

Used by desktop printers worldwide, DT is used to image to countless objects and works exceptionally well on both hard and soft substrates.

High color yield

More transferred color on your substrate with less ink left on your print-sheet.

APPLICATIONS

- Soft and hard substrates
 Epson desktop sheet and roll printers
 - Ricoh and Virtuoso desktop printers





TexPrint®DT Properties

	TexPrint®DTXP light	TexPrint®DTR heavy				
Description	DeskTop (light) Sheets	DeskTop (heavy) Sheets				
Basis Weight	105 gsm	120 gsm				
Thickness	140 μm	139.7 μm				
Bulk Pack	Available	Available				
Standard Desktop Sheet Sizes						
A2 (420.0 mm x 594.0 mm)	•					
A3 (297.0 mm x 420.0 mm)	•	•				
A4 (210.0 mm x 297.0 mm)	•	•				
102.0 mm x 241.0 mm (mug)	•	•				
102.0 mm x 229.0 mm (mug)	•	•				
89.0 mm x 232.0 mm (mug)	•	•				
89.0 mm x 229.0 mm (mug)	•	•				
3.5" x 9" (mug)		•				
126" / 320.0 cm		•				
4" x 9.5" (mug)		•				
8.5" x 11"	•	•				
8.5" x 14"	•	•				
11" x 17"	•	•				
13" x 19"	•	•				

Recommended Printing Conditions: 23-25 OC, 45-55% Humidity

GSM	Thickness (μm)	Application	Ink Load	Transfer Efficiency	Ink Drying
58	66				É
72	84				á á á á á



Beaver Paper Headquarters

2420 Tech Center Parkway, Bldg. 140 Lawrenceville, GA 30043 USA Contact Customer Service & Sales

📞 +1770-935-5080 x1 | 🔀 orders@beaverpaper.com

Beaver Paper GmbH

Im Lossenfeld 19, 77731 Wilstätt Germany **Contact Customer Service** customerservices@beaverpaper.de

Authorized Distributor

