

# TexPrint<sup>®</sup>UT

## UTILITY TEXTILE GRADE DYE-SUBLIMATION PRINT PAPER

Easy-to-work-with TexPrint<sup>®</sup>UT papers feature economical ink usage, highest color yields and powerful economics in cost conscious, high-volume textile printing environments. TexPrint<sup>®</sup>UT papers are not designed for hard, smooth, or non-porous substrates.



### FEATURES AND BENEFITS

#### Flatness

TexPrint<sup>®</sup>UT lays flat. Prints flat. Resists cockling even under heavy ink loads. No head strikes, no worries.

#### Waste reduction

Available in individually boxed or palletized packaging. Volume users can save time and labor by ordering bulk packaging.

#### Fast ink absorption

Easily keeps pace with the fastest commercial textile printers without offsetting.

#### Highest dye-gas output

More color, less ink. More color on your fabric and less ink left on your print sheet.

#### Largest selection of basis weights, widths and roll lengths to mini jumbo

Get exactly the right put-up for your print environment with less waste, fewer roll changes and more up-time.

#### Faster transfers

TexPrint<sup>®</sup>UT allows heat to migrate through the print sheet quicker, allowing lower calender dwell times and faster transfer speeds, while delivering the richest and deepest dye-gas penetration.

### APPLICATIONS













- Banners • Blinds • Fashion Textiles • Home Décor • Soft Signage
- Textiles • Trade Show Exhibits







# TexPrint® UT Properties

	TexPrint® UT 58	TexPrint® UT 72	TexPrint® UT 92-Elite
Basis Weight	58 gsm	72 gsm	92 gsm
Thickness	75 µm	88 µm	110 µm
Core I.D.	76 mm / 3"	76 mm / 3"	76 mm / 3"

	Standard Widths		
24" / 61.0 cm			●
36" / 91.4 cm		●	●
44" / 111.8 cm	●	●	●
54" / 137.2 cm	●	●	
64" / 162.0 cm	●	●	●
75" / 190.0 cm	●	●	●
104" / 264.0 cm			●
126" / 320.0 cm	●	●	●

## Recommended Printing Conditions: 23-25 OC, 45-55% Humidity

GSM	Thickness (µm)	Application	Ink Load	Transfer Efficiency	Ink Drying
58	66				
72	84				
92	109				

 Apparel	 Sports Apparel
 Banners/Signage	 Hard Surfaces
 Home Décor	 Fashion

Authorized Distributor

### Beaver Paper Headquarters

2420 Tech Center Parkway, Bldg. 140  
Lawrenceville, GA 30043 USA

Contact Customer Service & Sales

+1 770-935-5080 x1 | [orders@beaverpaper.com](mailto:orders@beaverpaper.com)

### Beaver Paper GmbH

Im Lossenfeld 19, 77731 Wilstätt Germany

Contact Customer Service

[customerservices@beaverpaper.de](mailto:customerservices@beaverpaper.de)

[www.beaverpaper.com](http://www.beaverpaper.com) +1 770-935-5080