

	Asphalt Art®	TexWalk®	TexWalk® Smooth and TexWalk® Canvas	CatWalk®	ClearWalk®	GloBrite®	SideWalk®	Smooth & Groove®	SportWalk®	TenaciousTac® 1, TenaciousTac® 2 TenaciousTac® 2CR TenaciousTac® 4	WallPro™ 3	WallPro™ 4	ARMORLam® 5	ARMORLam® 15	ARMORLam® 23
<b>Compatible Inks</b>	UV & Latex	Solvent, Eco-Solvent, UV, Latex, Offset	Solvent, Eco-Solvent, UV, Screen, Latex	Solvent, Eco-Solvent, UV, Latex, Offset	Solvent, Eco-Solvent, UV, Latex	Solvent, Eco-Solvent, UV, Latex, and Thermal Transfer Systems	UV, Latex, True-Solvent	UV inkjet, latex, solvent and eco-solvent	Solvent, Eco-Solvent, UV, Latex	Solvent, Eco-Solvent, UV, Latex	Solvent, Eco-Solvent, UV, Latex, Offset	UV, Latex, Offset	N/A	UV	N/A
<b>Durability</b>	Up to 12 months	Up to 4+ months on floors indoors, 36+ months on walls indoors; 1-3 months outdoor on smooth surfaces	36+ months on walls indoors; 1-3 months outdoor on smooth surfaces	Up to 3 months indoors	Up to 3 months indoors	24-36 months on walls indoors	Up to 12 Months	Up to 12 months Product requires the use of AMORLam™ 23 for non-slip rating and durability.	Up to 1 week outdoor	5+ years when used with over-laminate	60 months	24 months	6 to 12 months	12+ Months	12+ Months
<b>Roll Sizes</b>	24" x 10' 48" x 33' 48" x 100'	23" x 10' 48" x 82' 48" x 164'	23" x 10' 48" x 82'	27" x 10' 54" x 33' 54" x 100'	27" x 10' 54" x 33' 54" x 100'	27" x 10' 54" x 50' 54" x 150'	27" x 10' 54" x 75' 54" x 150' 54" x 300'	47"x300' 47"x100' 47"x50'	27" x 10' 54" x 33' 54" x 100'	27" x 10' 54" x 150'	27" x 10' 54" x 150'	27" x 10' 54" x 150'	27" x 10' 54" x 150'	27" x 10' 54" x 150'	27" x 10' 54" x 50' 54" x 100'
<b>Applied Thickness Substrate &amp; (Adhesive)</b>	23 mil	14 mil	14 mil	20 mil	20 mil	9 mil	16 mil	9 mil	23 mil	4 mil, 5 mil and 7 mil	4 mil	5 mil	5 mil	15 mil	23 mil
<b>Rough Surfaces</b>	Yes	Medium to light	Medium to light	No	No	No	Yes	Yes	Medium to light	Yes	No	No	No	No	No
<b>Type of Traffic</b>	Pedestrian and Vehicle Traffic*	Pedestrian		Pedestrian	Pedestrian	N/A	Pedestrian	Pedestrian and Vehicle Traffic*	Pedestrian	N/A	N/A	N/A	Pedestrian	Pedestrian	Pedestrian
<b>Indoor Use</b>	Yes concrete floors	Yes	Yes	Yes	Yes	Yes	Yes concrete floors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Outdoor Use</b>	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes	Yes	No	No	No	Yes	Yes
<b>Repositionable</b>	No	Yes	Yes	No	No	Yes	No	No	No	No	Yes	Yes	No	No	No
<b>Wall Applications</b>	Outdoor Wall Surfaces	Yes	Yes	No	No	Yes	Outdoor Wall Surfaces	Outdoor Wall Surfaces	No	N/A	Yes	Yes	Yes	No	No
<b>Common Uses</b>	Sports arena, Race tracks, Parades, Retail stores, Marathons, Bike events	Trade show, Retail POP, Wayfinding; S hort term outdoor on smooth surfaces	Wall coverings, wall accents and décor	Retail POP, Directional and Safety signage	Retail POP, Directional and Safety signage	Events, Safety and Promotional signage, Wayfinding, Creation of Retail and other environments	Sports arena, Race tracks, Parades, Retail stores, Marathons, Bike events	Sporting Events Retail Entrances Cultural Events Restaurants Office Hours on Exterior Wall	Marathons, Parades, Retail stores, Mall graphics	Labels and signs for hard to stick to surfaces such as LSE plastic and MDF board	Wall coverings, wall accents and décor. Can be used for floor graphics when combined with Jessup Overlam.	Wall coverings, wall accents and décor. Can be used for floor graphics when combined with	Medium duty laminate for floor graphics	Durable over-laminate for long lasting floor graphics. Slip resistant when dry.	Heavy duty over-laminate for long lasting floor graphics.
<b>Certifications</b>															
	ASTM D-2047 NSFI Certified UL 410 R12	ASTM D-2047 ASTM E-84 Class A CCC-W-408D Type I UL 410	ASTM D-2047 ASTM E-84 Class A CCC-W-408D Type I	ASTM D-2047 UL 410	ASTM D-2047 UL 410		NSFI Passed - B101.1 NSFI Passed - B101.3 UL 410 R13	ASTM E-84 Class A certified	ASTM D-2047 UL 410				ASTM D-2047 UL 410 R9	OSHA, ADA NSFI B101.1 B101.3 R11	ASTM D-2047 UL 410

\*Not intended for turning wheels on graphic.